

TÚNEIS DE PROCESSOS CONTÍNUOS

CONTINUOUS PROCESS TUNNELS



Tunnel Microwaves TMW 75
Túnel Micro-ondas TMW 75



Tunnel Microwaves TMW 150
Túnel Micro ondas TMW 150

MICRO WAVE TUNNEL TMW 75
TÚNEL MICROONDAS TMW 75

Frequency Frequência	915 MHz 896 MHz (Great-Britain) 922 MHz (Australia / New Zealand)
MW power MW Potência	1 x 75 kW
Mains Principal	100 KVA
Voltage Voltagem	400 V, 3 phases, 50/60 Hz
Cooling Resfriamento	By water
Capacity Capacidade	5 t to 6 t/h from -20 °C to -8 °C/-6 °C 3 t to 4 t/h from -20 °C to -6 °C/-4 °C 2 t to 3 t/h from -20 °C to -4 °C/-2 °C
Size Dimensões	L: 9 m / W: 3 m / H: 1.8 m

MICRO WAVE TUNNEL TMW 150
TÚNEL MICROONDAS TMW 150

Frequency Frequência	915 MHz 896 MHz (Great-Britain) 922 MHz (Australia / New Zealand)
MW power MW Potência	2 x 75 kW
Mains Principal	200 KVA
Voltage Voltagem	400 V, 3 phases, 50/60 Hz
Cooling Resfriamento	By water
Capacity Capacidade	10 t to 12 t/h from -20 °C to -8 °C/-6 °C 6 t to 8 t/h from -20 °C to -6 °C/-4 °C 4 t to 6 t/h from -20 °C to -4 °C/-2 °C
Size Dimensões	L: 12 m / W: 3 m / H: 1.8 m



MICRO WAVE TUNNEL TMW 225
TÚNEL MICRO ONDAS TMW 225

MICRO WAVE TUNNEL TMW 225
TÚNEL MICROONDAS TMW 225

Frequency Frequência	915 MHz 896 MHz (Great-Britain) 922 MHz (Australia / New Zealand)
MW power MW Potência	3 x 75 kW
Mains Principal	300 KVA
Voltage Voltagem	400 V, 3 phases, 50/60 Hz
Cooling Resfriamento	By water
Capacity Capacidade	15 t to 18 t/h from -20 °C to -8 °C/-6 °C 9 t to 12 t/h from -20 °C to -6 °C/-4 °C 6 t to 9 t/h from -20 °C to -4 °C/-2 °C
Size Dimensões	L: 15 m / W: 3 m / H: 1.8 m

MICRO WAVE TUNNEL TMW 300
TÚNEL MICROONDAS TMW

Frequency Frequência	915 MHz 896 MHz (Great-Britain) 922 MHz (Australia / New Zealand)
MW power MW Potência	4 x 75 kW
Mains Principal	400 KVA
Voltage Voltagem	400 V, 3 phases, 50/60 Hz
Cooling Resfriamento	By water
Capacity Capacidade	20 t to 24 t/h from -20 °C to -8 °C/-6 °C 12 t to 16 t/h from -20 °C to -6 °C/-4 °C 8 t to 12 t/h from -20 °C to -4 °C/-2 °C
Size Dimensões	L: 18 m / W: 3 m / H: 1.8 m

A capacidade depende da temperatura final requerida, formato dos blocos e ainda nível de gordura.

Capacity depends upon required final temperature, shape of the blocks and also upon level of lean or fat.